

Universal Paste / non-woven paste

1. Material

Type of material: Powder paste with synthetic resin.

Intended use: Suitable for all standard wallpapers.

Packaging sizes:

Artikel-no.	EAN	Packaging type	weight
076046	40 51315 46684 1	plastic	200 g
076045	40 00776 07604 5	cardboard	250 g
076052	40 00776 07605 2	cardboard	250 g
076073	40 51315 66401 8	cardboard	500 g

2. Special properties

Easy to mix and lump-free application, very economical, excellent adhesive strength with good correction possibilities (so-called repositioning), dries without stains (even on fresh dry plaster), lime and cement resistant and solvent-free.

3. Technical data:

Raw material base: starch ether, polyvinyl acetate powder and additives

Bulk density: approx. 0,44 g/cm³

pH-value (aqueous solution): 8

Solubility: ready for use after 15 minutes.

Drying time: 12-24 hours

4. Application and coverage

Application	Pack size 200g		Pack size 250g		Pack size 500g	
	water quantity	coverage	water quantity	coverage	water quantity	coverage
Pre-paste	8 l	approx. 60-80 m ²	10 l	approx. 75-100 m ²	20 l	approx. 150-200 m ²
Paper wallpaper	5 l	approx. 31 m ² approx. 6 Euro-rolls*	6 l	approx. 38 m ² approx. 7 Euro-rolls*	12 l	approx. 76 m ² ca. 15 Euro-rolls*
Satin, non-woven and textured wallpapers	4 l	approx. 25 m ² approx. 5 Euro-rolls*	5 l	approx. 31 m ² approx. 6 Euro-rolls*	11 l	approx. 69 m ² ca. 14 Euro-rolls*
Glass fabric	3 l	approx. 10-15 m ² approx. 2-3 Euro-rolls*	4 l	approx. 13-22 m ² approx. 3-4 Euro-rolls*	9 l	approx. 30-45 m ² ca. 6-9 Euro-rolls*

* Dimensions of a Euro roll: approx. 10,05 m x 0,53 m, i.e. approx. 5 m².

5. processing instructions

Substrate pre-treatment: Remove all old wallpaper. The surface to be wallpapered must be dry, clean, firm, stable, even and slightly absorbent. Fill cracks and holes with filler. Paint a neutral-coloured substrate, otherwise apply a white pigmented primer. Pre-paste highly absorbent substrate materials according to the table.

Application: Pour clean cold water into a container and stir in the contents of the pack, stirring continuously; see table for quantity of water and paste. After **2 minutes**, whisk the paste again vigorously; this prevents lumps from forming. After a total of **15 minutes**, whisk the mixture again vigorously, then the paste is ready for use.

Do not use if the substrate or room temperature is below + 5 °C. Stirred paste can be used for up to 7 days in a well-sealed container.

Wallpapering: Paste wallpaper or walls evenly in accordance with the application instructions, allow to soften if necessary and then wallpaper.

Paste residue: Remove any paste residue on the front of the wallpaper immediately with a damp cloth.

Tool cleaning: Clean with cold water immediately after use.

6. other information

Protection and safety instructions: Do not inhale paste dust. If the dry or wet paste comes into contact with the eyes, rinse them with clean water. For further information, please refer to the safety data sheet: www.as-creation.com

Storage: Store in a cool, dry place. Keep out of reach of children.

Disposal: Only dispose of empty containers for recycling (waste paper or plastic). Dried material residues can be disposed of with household waste or as construction site waste. EWC waste code no. EWC 08 04 14.

* * *

Anmerkung:

Alle Auskünfte und Daten in diesem Informationsblatt entsprechen unseren Praxiserfahrungen und Laboruntersuchungen und basieren auf dem heutigen Stand der Technik. Sie können jedoch nur allgemeine Hinweise darstellen, die keine Eigenschaftszusicherung beinhalten. Da die Bedingungen, unter denen Lagerung, Transport und Verarbeitung erfolgen, außerhalb unseres Einflussbereiches liegen, kann aus den Hinweisen keine rechtliche Verbindlichkeit abgeleitet werden. Es obliegt dem Anwender, die Produkte auf ihre Eignung für den von ihm vorgesehenen Verwendungszweck unter den jeweiligen Objektbedingungen zu prüfen.